

Prestige Classic 210006



Features

- ▶ Light, compact and portable, weighs only 9.9 pounds.
- ▶ Single, one step operation.
- ▶ Fully automatic.
- ▶ Large capacity chamber: 8" dia x 9" deep
- ▶ Safe and reliable.

Technical Specifications

- ▶ Temperature: 121° C (250° F)
- ▶ Sterilization Time: 16 minutes
- ▶ Total cycle Time: 26 minutes

Advanced Design

- ▶ A simple, one step operation starts the cycle
- ▶ Large sequence indicators show: "Power unit" - "Cycle in Progress" - "Sterilization in Process" - "Cycle is Successful" or "Cycle has Failed"
- ▶ An interlock system prevents the lid from being removed while pressure remains in the vessel
- ▶ A two stage "over pressure" protection system incorporates a calibrated Pressure Release Valve and a Gasket Offset Device
- ▶ Electronic detectors turn off the power if there is insufficient water
- ▶ Lifetime Guarantee on Heating Element
- ▶ Extended Life Green Gasket
- ▶ For your assurance of quality, each autoclave is computer tested and issued with a unique Performance Test Certificate showing that the parameters for successful sterilization have been met

Recommendation

Steam sterilization or autoclaving, is the preferred method for eliminating the risk of cross infection through contaminated instruments and the only one recommended throughout the world by healthcare professionals including the W.H.O. (World Healthcare Organization)